



油润滑旋片式真空泵。流量从50至180 m<sup>3</sup>/hr, 极限真空0.1 mbar(绝对值)。法兰式电机, 转子两侧装有轴承, 装有油/气热交换器。内置筛网过滤器, 真空逆止阀, 气镇阀, 保护罩和油分离器。


法兰式电机符合 DIN EN 60034 标准, 保护标准 IP 54, 绝缘等级 F。

Oil flooded rotary vane vacuum pump with capacities ranging from 50 to 180 m<sup>3</sup>/hr and an ultimate vacuum of 0.1 mbar (abs.).


Flange motor, bearings on both sides of the rotor, oil/air heat exchanger. Fitted as standard with fine mesh filter, vacuum non-return valve, gas ballast valve, protection cover and oil separator.

Flange mounted motors comply with DIN EN 60034, have IP 54 protection and insulation class F.

### 50 Hz 选型图 • Selection diagram



### 60 Hz 选型图 • Selection diagram



VC		50	75	100	150
额定流量	m <sup>3</sup> /h	50 Hz	50	70	100
Nominal capacity		60 Hz	60	84	120
极限真空	mbar (abs.)*			0,1	
Ultimate partial pressure					
电机类型	3~	50 Hz	200-255 / 346-440V ± 5%		230/400V±10%
Motor version		60 Hz	200-277 / 346-480V ± 5%		380/660V
电机功率	kW	50 Hz	1,25	1,85	3,0
Motor rating		60 Hz	1,5	2,2	3,6
电流	A	50 Hz	6,9 / 4,0	8,7 / 5,0	11,4 / 6,6
Current drawn		60 Hz	7,6 / 4,4	9,4 / 5,4	13,7 / 7,9
转速	min <sup>-1</sup>	50 Hz		1450	
Speed		60 Hz		1740	
平均噪音	dB(A)	50 Hz	64	64	66
Average noise level	→ DIN45635	60 Hz	67	68	69
最大重量	kg	50 Hz	57	59	88
Maximum weight		60 Hz	57	59	90
油量	l		3,0	3,0	3,5
Oil capacity					